

Wireless Long-Range Transmitter for CCTV IP Camera

WI-CPE515H-KIT



Overview

WI-CPE515H-KIT is designed to provide a cost-effective wireless network solution for video surveillance and data transmission. Adopting single-band 5GHz frequency, WI-CPE515H-KIT provides wireless speed of up to 300Mbps. Supporting PTP and PTMP(point-to-point and point-to-multipoint), WI-CPE515H-KIT provides flexible networking modes in outdoor wireless deployment. Featuring an 16dBi directional antenna, WI-CPE515H-KIT provide great performance in sustaining a stable signal for the wireless network.

Professional performance and user-friendly design make WI-CPE515H-KIT an ideal choice for business and CCTV applications.

Features

Long-Distance Data Transmission Up to 8km

With a high-performance 16 dBi Directional Antenna, WI-CPE515H-KIT long-distance wireless network transmission can be up to 8km. Besides, it provides an efficient way to pick up and maintain a stable signal for the wireless network.

Professional Outdoor Waterproof Design

Equipped with a durable IP65 waterproof enclosure and high-quality hardware design, WI-CPE515H-KIT can work in almost any climate, which ensures all-weather stability.

PTP/PTMP

WI-CPE513P-KIT supports two networking modes composed of PTP and PTMP(point-to-point and point-to-multipoint), which flexibly suits different outdoor network solution.

24V PoE Input Support

Simplifying installation by transmitting power and data over a single Ethernet cable, eliminating the need for additional power outlets.

Wi-Tek Cloud Management Platform

Wi-Tek Cloud's quick configuration provide reliable performance, visual management, and real-time monitoring, enhancing the efficiency of device management.



Specifications

Model	WI-CPE515H-KIT
Hardware Features	
Version	V1
Memory	DDR2: 64MB Flash: 8MB
Interface	2*10/100Mbps RJ45 Port 1*Reset Button
Power Supply	24V Passive PoE Input
Power Consumption (max)	6W
Package Dimension(L x W x H)	226*226*223mm
Product dimension	200*200*131mm
Product Weight	0.46*2kg
Package Weight	1.65kg
ESD Protection	Contact discharge: ±6kV, Air discharge: ±8kV
Surge Immunity	Common mode: 2kV, Differential mode: 1kV
IP Level	IP65
Wireless Features	
Standards	IEEE 802.11a/n
Data Rates	300Mbps
MIMO	2 x 2
Antenna	16dBi
Half Power Beamwidth (Typ.)	Horizontal: 30°, Vertical: 30°
Frequency	5.18 ~ 5.825GHz *Please follow national regulations to select the appropriate frequency.
Channel Width	20/40MHz
Transmit Power	Up to 27 dBm (country dependent)
Recommend Distance	8km
Software Features	

Wireless Mode	Basic Station/CPE/Repeater/WISP
Network	LAN: Static IP, Dynamic IP, PPPoE Client WAN(WISP mode): Static IP, Dynamic IP, PPPoE Client DHCP Server(Only WISP mode) VLAN: IEEE 802.1Q VLAN Passthrough
Wireless	Wireless Disable OR Enable Modify default SSID SSID Hiding Wireless Security: WPA-TKIP, WPA2-AES, WPA1/WPA2-Mixed, WPA/WPA2-Enterprise
RF Parameter	Adjustable Country Auto Channel Width Selection Automatic Frequency Selection Adjustable Transmission Power Max Associated STA (default: 128) Weak Signal Rejection Threshold(default: -95dBm) User Isolation(default: disabled) Supports Wi-Fi Multimedia (WMM) RTS/CTS Threshold (default: 2347)
Advanced	Spectrum Scheduled Reboot Ping Watchdog NTP Server
Status Monitoring	Base Info: LAN/WAN Info, Wireless Info, System Info Radio Status Real Time Flow Chart Wireless Terminal Station SSID List DHCP Client(For WISP mode) ARP Table Routing Table
Management	Quickly scan devices by discovery tools Web-based management by locally Support remote management by cloud platforms and applications
System Tool	PING, TRACERT, Speed Test
Environment	Operating Temperature: -40°C ~ 70°C(-40°F ~158°F) Storage Temperature: -40°C ~ 85°C(-40°F ~ 185°F) Operating Humidity: 10% ~ 95% (non-condensing) Storage Humidity: 5% ~ 95% (non-condensing)
Others	
Certification	CE, FCC, RoHS, UKCA, RCM

Package Contents

Welcome to order our products. After purchasing, you will receive:

Items	Quantity
WI-CPE515H	2 pcs
24V Passive PoE Adapters	2 pcs
Pole Mount Kits	2 pcs
Quick Installation Guide	1 pcs



Wireless-Tek Technology Limited

Address: Biaofan Technology Building 402, Bao'an street,
Baoan District, Shenzhen City, Guangdong, China

Website: www.wireless-tek.com

Tel: 86-0755-32811290

Email: sales@wireless-tek.com

Technical Support: tech@wireless-tek.com



Technical Support



Cloud Management



Company Website